



## SS Series

### Stainless Steel Water Hammer Arrestor

#### Size: DN15-DN25

Watts SS Series pre-charged all stainless steel shock arrestor with stainless steel bellows and male IPS threaded connection.

#### Features

- Bellow Type
- Nitrogen Pre-charged bellows
- SS304 construction

#### Pressure-Temperature

- Pressure: 150 psi working pressure, 250 psi static pressure
- Temperature Range: -73 °C ~149 °C

#### Material

NO.	Component	Material
1	Body	SS 304
2	Bellows	SS 304
3	Connection	SS 304
4	Pre-charge fluid	Nitrogen

#### Technical Data

Model	SS-AA	SS-A	SS-B	SS-C	SS-D	SS-E	SS-F
Fix. units	1 -11	1-11	12-32	33-60	61-113	114-154	155-330
Conn.	1/2"	3/4"	1"	1"	1"	1"	1"
A	3 1/4"	3 1/4"	3 1/4"	3 1/4"	3 1/4"	3 1/4"	3 1/4"
B	3 1/4"	3 1/4"	4"	4 5/16"	5 1/4"	7"	7"



#### Installation

May be installed in new or existing plumbing systems with a standard pipe tee vertically, horizontally, or at any angle. SS Series are factory air charged and permanently sealed. They may be installed in concealed locations without access panels and are not rechargeable in the field

